I'm not robot

reCAPTCHA

Continue

I'm not robot

reCAPTCHA

Update from two tables in sql server

Update query from two tables in sql server. How to update data from two tables in sql server.

Assuming that the goal is not to repeat , and ignoring some significant problems with the scheme (included because it is necessary to mark both a user and all their orders as inactive?), You can do it in This way by filling users affected by the first update in a #temp table, and then joining the update on the one for water. Create Table #u (ID INT), UPDATE DBO. [USER] - Keyword, and why is it no plural as orders? Set Active = 0 output entered. ID INTO #U WHERE ACTIVE = 1 - Do not disturb the upgrade of the rows already set in this way - and ; Update or Set O.Active = 0 from dbo.orordini as or inner join #u as u on o.userid = u.id where o.active = 1; - again updates only the rows that must change Drop Table #u; If you are not interested in repeating then the second question could be: update or set o.active = 0 from dbo.orordini as or inner join dbo. [User] as u on o.userid = u.id where or .Active = 1 and u.active = 0 --and tsql Discover tips and tricks on how to master your data with SolarWindsÂ® DataOps solutions, which are designed to help you optimize the essential database activities, database projects and data-based application development . We show you how to save time on the duty tasks of the boring but critical database. Problems We use the databases to store information in the tables. Once the data is written to these tables, it is often required to update certain fields during data duration. In the SQL language, we can use the update instruction to achieve this goal. In this tutorial we cover several examples of how to use the Update instruction. Solution In this suggestion, we will show you how you can use the Update T-SQL statement to update the data to a database table. We will use the SQL database of the AdventureWorks 2017 sample. If you want to follow, you can download the sample database and restore it to the system. You can copy paste queries and run them to the machine using Microsoft SQL Server Management Studio (SSMS). Simple syntax sql update a simple update statement can take the following format: column set of the table update = ; Update a single column Let's take a look at the fictitious example in which [Sickleavehors] is the column name with the int database type in [HumanResources]. Table. The [SICKLEAVEHORS] is set to 0, which is the clause set to update existing records. Here is the Transact-SQL sample Code: Update [HumanResources]. Set [sickleavehours] = 0; This sets all existing data rows for the SICKLEAVEHORS column in the value dependent table 0. It is also possible to use an expression that refers to the column itself. In this example, we are improving the Vacationhours column with 10%. UPDATE [Human Resources]. [Employee] SET [VacationHours] = [VacationHours] * 1.1; When UPDATE declaration is executed, SQL Server will take the current value of each row and multiplies it with 1.1. The result will be stored in the column. When you make the statement in SSMS, the message board will display how many rows have been updated by the statement:Examples for more columns You can also update more columns simultaneously, separating columns with a comma. In this statement, we also update the modified column of the table: update [HumanResources]. [Employee] Set [HolidayHour] = [Vacanzehour] * 1.1, [Modified] = GetDate (); You can refer to the columns of the same table, while they are also updated. Let's say for example we are restoring all hours of vacation to zero. At the same time, the hours of disease leave are updated based on the current value of vacation hours. Update [HumanResources]. [Employee] Set [HolidayHour] = 0, [Sickleavehours] = IIF ([holiday holiday]